

Factory Line: 800-363-2488

www.superchute.com

INTERLOCKING CAPTIVE SECTIONS



- The tightest compaction with slim 1" rim collars
- All plastic design
- No chains
- Lightweight
- Suitable for chute drops less than 20 ft (6 m)





Dust Control

Useful for deploying flowable materials such as rock, coal, woodchips, sand, fly ash, fine powders & other materials. As the mound rises, the telescopic chute is retracted with help of winches.

CHAIN LINKED SECTIONS





Applications

- Stockpiling ✓
- Loading trucks, railcars & ships ✓
- Use where high clearance is required ✓
- Discharge skirts can be added for additional dust control ✓

- Easy to add, remove, or separate sections
- Low profile 2" tall chain brackets
- Strong, durable linking system
- Ideal for both short and tall chutes
- Ouick to manufacture





CUSTOMIZED RETRACTION WINCHES

Each winch is designed & manufactured to suit the application.




Single Drum Winch



Dual Drum Tight Spacing



Dual Drum Wide Spacing



Multiple Drum

Winch Options:

- Radio remote control
- Rotary limit switches
- Paddle limit switches
- Heavy duty epoxy paint finish

Rigging Options:

- Pulleys
- Wire-rope assemblies
- Breakaway cables

Material Options









HMWPE

UHMWPE

METAL

HEAT RESISTANT

www.superchute.com Toll Free: 800-363-2488 Local: 514-365-6121 Fax: 514-365-8987

E-Mail: info@superchute.com

Superchute Ltd. 8810 Elmslie Road Montreal, Quebec Canada, H8R 1V6



- Made in Canada
- Consult the Superchute® reference guide or manual for more information
- For clients in the USA: Free Trade applies No import duties or taxes
- \bullet Superchute $^{\circledcirc}$ is a registered trademark of Superchute Ltd. (US Trademark 1737832)
- Printed in Canada